

Name		2 in 1 (801032-0452)	2 in 1 (801032-0453)	2 in 1 (801032-0454)
Model		PW-300	PW-400	PW-500
Price EUR:		1152	1350	1548
Inner material		SUS304	SUS304	SUS304
Inner thickness (mm)		1.4	1.5	1.5
Outer casing		Color steel plate	Color steel plate	Color steel plate
Outer thickness (mm)		0.4	0.4	0.4
Max working pressure (bar)		8	8	8
Hot water tank	Volume	200L	260L	330L
	Circularion import and export	G1" M	G1" M	G1" M
	Hot and cold water in and outlet	G3/4" M	G3/4" M	G3/4" M
	Anode Rod port	G3/4" F	G3/4" F	G3/4" F
	P/TP valve port	G3/4" F	G3/4" F	G3/4" F
	Electric heater port	G1" F	G1" F	G1" F
	Electric heating	3kW	3kW	3kW
	Sewage Outlet	G3/4" F	G3/4" F	G3/4" F
	Coil material	SUS304	SUS304	SUS304
	Coil thickness mm	0.3	0.3	0.3
	Coil specification	φ25mmx15mBellows	φ25mmx20mBellows	φ25mmx25mBellows
	Coil area/m²	1.6	2.2	2.7
Buffer tank	Volume	80L	120L	120L
	Circularion import and export1	G1" F	G1" F	G1" F
	Circularion import and export2	G1" F	G1" F	G1" F
	Electric heater port	N/A	N/A	N/A
	Electric heating	N/A	N/A	N/A
	Sewage Outlet	G3/4" F	G3/4" F	G3/4" F
	exhaust vent	G1/2" F	G1/2" F	G1/2" F
Suitable for heating capacity of heat pump		8kW	13kW	23kW
Product Size mm		φ 560*1845	φ 700*1590	φ700*1875
Package dimensions mm		640*640*1950	790*790*1680	790*790*1950
Net weight kg		60	72	85
Gross weight kg		65	79	91